

# Installation Instructions

# 4 LED Stop/Turn/Tail/Tail/Backup/ Strobe Lights 4" Round - 5624424 & 6" Oval - 5626424

## Patent Pending Combination Light Optic Design

## **Features:**

- Integrated Warning, Reverse and Stop/Turn/Tail
- Grommet Mount
- SAE J 595 Class 1 Rated Amber Strobe
- Waterproof

## **Specifications:**

Voltage: 12-24VDCAmps: 0.53 Amp @ 12V

Watts: 7W# of LED's: 24Flash Patterns: 57

Operating Temperature: -22°F to 158°F
Certifications: SAE J595, FMVSS 108


# **Wiring Configuration:**

- Red Connect +VDC to Wire to activate Stop/Turn function
- White Ground wire. Required for all functions.
- Black Tail light
- Gray Reverse light
- Brown Amber Strobe light
- Blue White Strobe light
- Yellow Synchronization
- Green Alternation. With the power off, connect green wire and yellow to yellow of other light, their patterns will alternate when the lights are activated.
- Orange Flash pattern selection and reset.
  - To change the Flash patterns, apply +VDC for less than 1 second and release.
  - Flash pattern will be reset when Orange Wire is connected to Red Wire for more than 5 seconds.
  - \*\* Stop/Turn Function and Reverse Function Override Warning Light Function. \*\*






#### SYNC WIRING DIAGRAM



#### ALTERNATING WIRING DIAGRAM





## **Flash Patterns**

| PATTERN | LED COLOR | DESCRIPTION                             |
|---------|-----------|---|
| 1       | Amber     | Cycle Pattern 2 to Pattern 19           |
| 2       | Amber     | Single Flash Alternately                |
| 3       | Amber     | Double Flash Alternately                |
| 4       | Amber     | Quad Flash Alternately                  |
| 5       | Amber     | Quad Flash + Single Flash Alternately   |
| 6       | Amber     | 8 Flash Alternately                     |
| 7       | Amber     | Quad Flash / 4 Single Flash Alternately |
| 8       | Amber     | 4 Single Sohrt Flash + 4 Single Flash   |
| 9       | Amber     | Single Flash                            |
| 10      | Amber     | Double Flash                            |
| 11      | Amber     | Slow-Single Flash                       |
| 12      | Amber     | Slow-Double Flash                       |
| 13      | Amber     | Quad Flash                              |
| 14      | Amber     | Quad Flash + Single Flash               |
| 15      | Amber     | 8 Short Flash                           |
| 16      | Amber     | 4 Single Sohrt Flash + 4 Single Flash   |
| 17      | Amber     | 11 Short Flash + 5 Single Flash         |
| 18      | Amber     | Steady burn + Double Flash              |
| 19      | Amber     | Steady burn                             |
| 20      | White     | Cycle Pattern 2 to Pattern 19           |
| 21      | White     | Single Flash Alternately                |
| 22      | White     | Double Flash Alternately                |
| 23      | White     | Quad Flash Alternately                  |
| 24      | White     | Quad Flash + Single Flash Alternately   |
| 25      | White     | 8 Flash Alternately                     |
| 26      | White     | Quad Flash / 4 Single Flash Alternately |
| 27      | White     | 4 Single Sohrt Flash + 4 Single Flash   |
| 28      | White     | Single Flash                            |
| 29      | White     | Double Flash                            |

| PATTERN | LED COLOR   | DESCRIPTION                             |
|---------|-------------|---|
|         |             |   |
| 30      | White       | Slow-Single Flash                       |
| 31      | White       | Slow-Double Flash                       |
| 32      | White       | Quad Flash                              |
| 33      | White       | Quad Flash + Single Flash               |
| 34      | White       | 8 Short Flash                           |
| 35      | White       | 4 Single Sohrt Flash + 4 Single Flash   |
| 36      | White       | 11 Short Flash + 5 Single Flash         |
| 37      | White       | Steady burn + Double Flash              |
| 38      | White       | Steady burn                             |
| 39      | Amber/White | Cycle Pattern 2 to Pattern 19           |
| 40      | Amber/White | Single Flash Alternately                |
| 41      | Amber/White | Double Flash Alternately                |
| 42      | Amber/White | Quad Flash Alternately                  |
| 43      | Amber/White | Quad Flash + Single Flash Alternately   |
| 44      | Amber/White | 8 Flash Alternately                     |
| 45      | Amber/White | Quad Flash / 4 Single Flash Alternately |
| 46      | Amber/White | 4 Single Sohrt Flash + 4 Single Flash   |
| 47      | Amber/White | Single Flash                            |
| 48      | Amber/White | Double Flash                            |
| 49      | Amber/White | Slow-Single Flash                       |
| 50      | Amber/White | Slow-Double Flash                       |
| 51      | Amber/White | Quad Flash                              |
| 52      | Amber/White | Quad Flash + Single Flash               |
| 53      | Amber/White | 8 Short Flash                           |
| 54      | Amber/White | 4 Single Sohrt Flash + 4 Single Flash   |
| 55      | Amber/White | 11 Short Flash + 5 Single Flash         |
| 56      | Amber/White | Steady burn + Double Flash              |
| 57      | Amber/White | Steady burn                             |

### **WARRANTY**

Buyers Products Co. warrants all truck/trailer hardware manufactured or distributed by it, to be free from defects in material and workmanship for a period of one year from date of shipment. Parts must be properly installed and used under normal conditions. Any product which has been altered, including modification, misuse, accident or lack of maintenance will not be considered under warranty. Normal wear is excluded. The sole responsibility of Buyers Products Co. under this warranty is limited to repairing or replacing any part or parts which are returned, prepaid, and are found to be defective by Buyers Products Co. Authorization from Buyers Products Co. must be obtained before returning any part. No charges for transportation or labor performed on Buyers' products will be allowed under this warranty.