



TORFLEX AXLE Series Information

SERIES	8	9	10L	10	11	12	12V	13	13G	13D
Capacity	600 lb - 1,100 lb	1,000 lb - 2,200 lb	2,500 lb - 3,000 lb	2,500 lb - 3,500 lb	3,600 lb - 6,000 lb	5,500 lb - 7,000 lb	5,500 lb - 7,200 lb	8,000 lb	9,000 lb - 10,000 lb	10,000 lb
Bracket Length	10"	10"	10"	10"	11"	12"	12"	13"	13"	13"
Bracket Width	2"	2"	2.5"	2.5"	2.5"	2.5"	2.5"	2.5"	2.5"	2.5"
Tube Size	1.75"	2.17"	2.62"	2.62"	3.03"	3.5"	3.5"	3.88"	3.88"	3.88"
Standard Spindle Length	11.5"	12.5"	Standard Only	Standard Only	14.5"	Standard Only	17.5"	17.5"	Standard Only	Standard Only
Short Spindle Length	9"	11.5"	N/A	N/A	13.5"	N/A	16.5"	16.5"	N/A	N/A
Possible Profiles	Low only	Low, High 3"	Low, High 3"	Low, High 3"	Low or High	Low or High	Low or High	Low or High	High only	High only
Brake Size	7" x 1-1/4" Electric 7" x 1-3/4" Hydraulic	7" x 1-1/4" Electric 7" x 1-3/4" Hydraulic	10" x 1-1/2"	10" x 2-1/4"	12" x 2"	12" x 2"	12-1/4" x 2-1/2"	12-1/4" x 3-3/8"	12-1/4" x 3-3/8"	12-1/4" x 4"
No. of Brake Flange Holes	4	4	4	4	5	5	4	4	7	7
Standard Bearing	Inner L44649	Inner L44649	Inner LM67048	Inner L68149	Inner 25580	Inner 25580	Inner 25580	Inner 25580	Inner 387A	Inner 395S
	Outer L44649	Outer L44649	Outer L44649	Outer L44649	Outer LM67048 15123	Outer 14125A	Outer 02475	Outer 02475	Outer 25580	Outer 387A
Bolt Patterns	4 on 4 5 on 4.5	4 on 4 5 on 4.5	5 on 4.5	5 on 4.5 5 on 4.75 5 on 5 5 on 5.5 6 on 5.5	6 on 5.5	8 on 6.5	8 on 6.5	8 on 6.5	8 on 6.5	8 on 6.5

BRAKE TYPES: ELECTRIC: Standard, Standard with Parking Feature or Nev-R-Adjust
 HYDRAULIC: Uni-Servo, Uni-Servo with Parking Feature, Duo-Servo, Free-Backing or Disc

Croft Trailer Supply, Inc. - Distribution Center

P.O. Box 300320 • Kansas City, MO 64130-0320 • 816-861-1001 • Fax 816-861-1881 • www.crofttrailer.com